

Heat Shrinkable Tubing

Quick Selection Chart

Type	Product	Shrink Ratio	Recovery Temp. (°C)	Operating Temp. (°C)	Voltage (V)	Flame Retardant	Adhesive	UL File No.	MIL Spec.	Available Colors																	
										Black	White	Yellow	Red	Blue	Green	Grey	Violet	Orange	Brown	Clear	Yellow/Green	Rust					
Single Wall Polyolefin	DUNBAR-1605	2:1	90	-55 ~ 105	600	✓		E319303		●	●	●	●	●	●	●	●	●	●	●	●	●					
	DUNBAR-1605G					✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	DUNBAR-1625					✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	DUNBAR-1625G					✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	DUNBAR-1625GT					✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	DUNBAR-1625LT			✓		-55 ~ 125	600		✓		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	DUNBAR-1625N			✓					●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	DUNBAR-1625T			✓					●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	DUNBAR-1635F			✓					-55 ~ 135	600	✓		MIL-DTL-23053 / 5	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	DUNBAR-1635F/YL/GN			✓							●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	DUNBAR-1635S	✓		MIL-DTL-23053 / 6	●	●	●	●			●	●	●	●	●	●	●	●	●	●	●	●	●	●			
	DUNBAR-3635S	2.5:1	110	-55 ~ 135	600	✓		E319303		●	●	●	●	●	●	●	●	●	●	●	●	●	●				
	DUNBAR-3625LT	3:1	80			✓			MIL-DTL-23053 / 5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
	DUNBAR-3635	3:1	90			✓			MIL-DTL-23053 / 5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	DUNBAR-4635	4:1	90			✓				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
DUNBAR-1625BS	2:1	130	✓				E319314			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
DUNBAR-1625W	3:2	120	✓			MIL-DTL-23053 / 4 C2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
DUNBAR-2690NW		80	✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
DUNBAR-2690NW-LT		80	✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
DUNBAR-3625WS	3:1	125	✓		600	✓	✓	E319314	MIL-DTL-23053 / 4 C1	●	●	●	●	●	●	●	●	●	●	●	●	●					
DUNBAR-3635W		120	✓	✓		MIL-DTL-23053 / 4 C3	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
DUNBAR-4635W		120	✓	✓		MIL-DTL-23053 / 4	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
DUNBAR-4635WS	4:1	130	✓		600	✓	✓	E319314		●	●	●	●	●	●	●	●	●	●	●	●	●					
DUNBAR-4635WT		120	✓	✓		MIL-DTL-23053 / 4	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
DUNBAR-4650WS		130	✓	✓			●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
DUNBAR-CATV	3:1	120	-55 ~ 125	1000	✓	✓	E319303			●	●	●	●	●	●	●	●	●	●	●	●	●					
DUNBAR-PHWT					✓	✓		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
DUNBAR-PHWT-FR					✓	✓		MIL-DTL-23053 / 15 C1	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
DUNBAR-PMWT					✓	✓			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
DUNBAR-PMWT-FR					✓	✓		MIL-DTL-23053 / 15 C2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Sertifications: LG: ISO 9001, QS 9000, ISO 14001, ISO/TS 16949

Underwriters Laboratories Inc. TUV (R86603)

RoSH

ABS Certificate of Type Approval

DNV Type Approval Certificate

EVERYWHERE YOU LIVE AND WORK

Motor Repair **800.774.4643**
OEM **800.805.4636**

