

ANSI X12 version 4010 855 Purchase Order Acknowledgement

VERSION: 1.0 FINAL

Author:	Superior Essex
Publication Date:	04/07/00
Trading Partner:	All



855

Purchase Order Acknowledgment

Functional Group=PR

This Draft Standard for Trial Use contains the format and establishes the data contents of the Purchase Order Acknowledgment Transaction Set (855) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to a seller's acknowledgment of a buyer's purchase order. This transaction set can also be used as notification of a vendor generated order. This usage advises a buyer that a vendor has or will ship merchandise as prearranged in their partnership.

Segments:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Used
	GS	Functional Group Header	M	1			Used

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BAK	Beginning Segment for Purchase Order Acknowledgment	M	1			Must use

<u>LOOP ID - N1</u>					<u>200</u>		
300	N1	Name	O	1			Used
420	MSG	Message Text	O	>1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
------------	-----------	---------------------	------------	----------------	---------------	--------------	--------------

<u>LOOP ID - PO1</u>					<u>100000</u>		
010	PO1	Baseline Item Data	O	1		N2/010	Used

<u>LOOP ID - PID</u>					<u>1000</u>		
050	PID	Product/Item Description	O	1			Used

<u>LOOP ID - ACK</u>					<u>104</u>		
270	ACK	Line Item Acknowledgment	O	1			Used

<u>LOOP ID - SLN</u>					<u>1000</u>		
490	SLN	Subline Item Detail	O	1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
------------	-----------	---------------------	------------	----------------	---------------	--------------	--------------

<u>LOOP ID - CTT</u>					<u>1</u>		
010	CTT	Transaction Totals	O	1		N3/010	Used



08/15/00						Purchase Order Acknowledgment - 855
020	AMT	Monetary Amount	O	1	N3/020	Used
030	SE	Transaction Set Trailer	M	1		Must use

Segments:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Used
	IEA	Interchange Control Trailer	M	1			Used

Notes:

- 2/010 PO102 is required.
- 3/010 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/020 If AMT is used in the summary area, then AMT01 will = TT and AMT02 will indicate total transaction amount as calculated by the sender.

ISA

Interchange Control Header

Pos:	Max: 1
- Mandatory	
Loop: N/A	Elements: 16

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier Description: Code to identify the type of information in the Authorization Information <u>Code Name</u> 00 No Authorization Information Present (No Meaningful Information in I02)	M	ID	2/2	Must use
ISA02	I02	Authorization Information Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)	M	AN	10/10	Must use
ISA03	I03	Security Information Qualifier Description: Code to identify the type of information in the Security Information <u>Code Name</u> 00 No Security Information Present (No Meaningful Information in I04)	M	ID	2/2	Must use
ISA04	I04	Security Information Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)	M	AN	10/10	Must use
ISA05	I05	Interchange ID Qualifier Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified <u>Code Name</u> 12 Phone (Telephone Companies)	M	ID	2/2	Must use
ISA06	I06	Interchange Sender ID Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element	M	AN	15/15	Must use
ISA07	I05	Interchange ID Qualifier Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified <u>Code Name</u> 01 Duns (Dun & Bradstreet) 09 X.121 (CCITT) 12 Phone (Telephone Companies) ZZ Mutually Defined	M	ID	2/2	Must use
ISA08	I07	Interchange Receiver ID Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other	M	AN	15/15	Must use



08/15/00

Purchase Order Acknowledgment - 855

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date Description: Date of the interchange	M	DT	6/6	Must use
ISA10	I09	Interchange Time Description: Time of the interchange	M	TM	4/4	Must use
ISA11	I10	Interchange Control Standards Identifier Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used.	M	ID	1/1	Must use
ISA12	I11	Interchange Control Version Number Description: This version number covers the interchange control segments <u>Code Name</u> 00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997	M	ID	5/5	Must use
ISA13	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	N0	9/9	Must use
ISA14	I13	Acknowledgment Requested Description: Code sent by the sender to request an interchange acknowledgment (TA1) <u>Code Name</u> 0 No Acknowledgment Requested	M	ID	1/1	Must use
ISA15	I14	Usage Indicator Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information <u>Code Name</u> P Production Data T Test Data	M	ID	1/1	Must use
ISA16	I15	Component Element Separator Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator	M		1/1	Must use

GS

Functional Group Header

Pos:	Max: 1
- Mandatory	
Loop: N/A	Elements: 8

To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code Description: Code identifying a group of application related transaction sets <u>Code Name</u> PR Purchase Order Acknowledgement (855)	M	ID	2/2	Must use
GS02	142	Application Sender's Code Description: Code identifying party sending transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS03	124	Application Receiver's Code Description: Code identifying party receiving transmission. Codes agreed to by trading partners	M	AN	2/15	Must use
GS04	373	Date Description: Date expressed as CCYYMMDD	M	DT	8/8	Must use
GS05	337	Time Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD	M	TM	4/8	Must use
GS06	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use
GS07	455	Responsible Agency Code Description: Code used in conjunction with Data Element 480 to identify the issuer of the standard <u>Code Name</u> X Accredited Standards Committee X12	M	ID	1/2	Must use
GS08	480	Version / Release / Industry Identifier Code Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed <u>Code Name</u> 004010 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997	M	AN	1/12	Must use

Semantics:

- GS04 is the group date.
- GS05 is the group time.
- The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

- A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST

Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set	M	ID	3/3	Must use
		<u>Code Name</u> 855 Purchase Order Acknowledgment				
ST02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

- The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BAK Beginning Segment for Purchase Order Acknowledgment

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

To indicate the beginning of the Purchase Order Acknowledgment Transaction Set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BAK01	353	Transaction Set Purpose Code Description: Code identifying purpose of transaction set <u>Code Name</u> 00 Original	M	ID	2/2	Must use
BAK02	587	Acknowledgment Type Description: Code specifying the type of acknowledgment <u>Code Name</u> AC Acknowledge - With Detail and Change	M	ID	2/2	Must use
BAK03	324	Purchase Order Number Description: Identifying number for Purchase Order assigned by the orderer/purchaser	M	AN	1/22	Must use
BAK04	373	Date Description: Date expressed as CCYYMMDD	M	DT	8/8	Must use

Semantics:

1. BAK04 is the date assigned by the purchaser to purchase order.
2. BAK08 is the seller's order number.
3. BAK09 is the date assigned by the sender to the acknowledgment.



N1

Name

Pos: 300	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual <u>Code Name</u> ST Ship To	M	ID	2/3	Must use
N102	93	Name Description: Free-form name	C	AN	1/60	Used
N103	66	Identification Code Qualifier Description: Code designating the system/method of code structure used for Identification Code (67) <u>Code Name</u> 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix 12 Telephone Number (Phone) 92 Assigned by Buyer or Buyer's Agent ZZ Mutually Defined	C	ID	1/2	Used
N104	67	Identification Code Description: Code identifying a party or other code	C	AN	2/80	Used

Syntax:

1. N102 R0203 -- At least one of N102 or N103 is required.
2. N103 P0304 -- If either N103 or N104 are present, then the others are required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

MSG Message Text

Pos: 420	Max: >1
Heading - Optional	
Loop: N1	Elements: 1

To provide a free-form format that allows the transmission of text information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-Form Message Text	M	AN	1/264	Must use

Description: Free-form message text

Syntax:

1. MSG03 C0302 -- If MSG03 is present, then MSG02 is required

Semantics:

1. MSG03 is the number of lines to advance before printing.

Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

PO1 Baseline Item Data

Pos: 010	Max: 1
Detail - Optional	
Loop: PO1	Elements: 10

To specify basic and most frequently used line item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO101	350	Assigned Identification Description: Alphanumeric characters assigned for differentiation within a transaction set	O	AN	1/20	Used
PO102	330	Quantity Ordered Description: Quantity ordered	C	R	1/15	Used
PO103	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	O	ID	2/2	Used
PO104	212	Unit Price Description: Price per unit of product, service, commodity, etc.	C	R	1/17	Used
PO106	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) <u>Code Name</u> BP Buyer's Part Number	C	ID	2/2	Used
PO107	234	Product/Service ID Description: Identifying number for a product or service	C	AN	1/48	Used
PO108	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) <u>Code Name</u> VP Vendor's (Seller's) Part Number	C	ID	2/2	Used
PO109	234	Product/Service ID Description: Identifying number for a product or service	C	AN	1/48	Used
PO110	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) <u>Code Name</u> UP U.P.C. Consumer Package Code (1-5-5-1)	C	ID	2/2	Used
PO111	234	Product/Service ID Description: Identifying number for a product or service	C	AN	1/48	Used

Syntax:

1. PO103 C0302 -- If PO103 is present, then PO102 is required
2. PO105 C0504 -- If PO105 is present, then PO104 is required
3. PO106 P0607 -- If either PO106 or PO107 are present, then the others are required.
4. PO108 P0809 -- If either PO108 or PO109 are present, then the others are required.
5. PO110 P1011 -- If either PO110 or PO111 are present, then the others are required.

PID

Product/Item Description

Pos: 050	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
PID01	349	Item Description Type Description: Code indicating the format of a description <table border="1"> <thead> <tr> <th><u>Code</u></th> <th><u>Name</u></th> </tr> </thead> <tbody> <tr> <td>F</td> <td>Free-form</td> </tr> </tbody> </table>	<u>Code</u>	<u>Name</u>	F	Free-form	M	ID	1/1	Must use
<u>Code</u>	<u>Name</u>									
F	Free-form									
PID05	352	Description Description: A free-form description to clarify the related data elements and their content	C	AN	1/80	Used				

Syntax:

1. PID04 C0403 -- If PID04 is present, then PID03 is required
2. PID04 R0405 -- At least one of PID04 or PID05 is required.
3. PID07 C0703 -- If PID07 is present, then PID03 is required
4. PID08 C0804 -- If PID08 is present, then PID04 is required
5. PID09 C0905 -- If PID09 is present, then PID05 is required

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.



ACK Line Item Acknowledgment

Pos: 270	Max: 1
Detail - Optional	
Loop: ACK	Elements: 5

To acknowledge the ordered quantities and specify the ready date for a specific line item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ACK01	668	Line Item Status Code Description: Code specifying the action taken by the seller on a line item requested by the buyer <u>Code Name</u> IA Item Accepted IC Item Accepted - Changes Made	M	ID	2/2	Must use
ACK02	380	Quantity Description: Numeric value of quantity	C	R	1/15	Used
ACK03	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	C	ID	2/2	Used
ACK04	374	Date/Time Qualifier Description: Code specifying type of date or time, or both date and time <u>Code Name</u> 010 Requested Ship 079 Promised for Shipment	O	ID	3/3	Used
ACK05	373	Date Description: Date expressed as CCYYMMDD	C	DT	8/8	Used

Syntax:

1. ACK02 P0203 -- If either ACK02 or ACK03 are present, then the others are required.
2. ACK04 C0405 -- If ACK04 is present, then ACK05 is required
3. ACK07 P0708 -- If either ACK07 or ACK08 are present, then the others are required.
4. ACK09 P0910 -- If either ACK09 or ACK10 are present, then the others are required.
5. ACK11 P1112 -- If either ACK11 or ACK12 are present, then the others are required.
6. ACK13 P1314 -- If either ACK13 or ACK14 are present, then the others are required.
7. ACK15 P1516 -- If either ACK15 or ACK16 are present, then the others are required.
8. ACK17 P1718 -- If either ACK17 or ACK18 are present, then the others are required.
9. ACK19 P1920 -- If either ACK19 or ACK20 are present, then the others are required.
10. ACK21 P2122 -- If either ACK21 or ACK22 are present, then the others are required.
11. ACK23 P2324 -- If either ACK23 or ACK24 are present, then the others are required.
12. ACK25 P2526 -- If either ACK25 or ACK26 are present, then the others are required.
13. ACK27 P2728 -- If either ACK27 or ACK28 are present, then the others are required.
14. ACK28 C282729 -- If 28 is present, then ACK27 and ACK29 are required.

Semantics:

1. ACK29 Industry Reason Code may be used to identify the item status. In addition, it may be used in conjunction with ACK01 to further clarify the status.



SLN Subline Item Detail

Pos: 490	Max: 1
Detail - Optional	
Loop: SLN	Elements: 4

To specify product subline detail item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SLN01	350	Assigned Identification Description: Alphanumeric characters assigned for differentiation within a transaction set	M	AN	1/20	Must use
SLN03	662	Relationship Code Description: Code indicating the relationship between entities <u>Code Name</u> I Included	M	ID	1/1	Must use
SLN04	380	Quantity Description: Numeric value of quantity	C	R	1/15	Used
SLN05	C001	Composite Unit of Measure Description: To identify a composite unit of measure(See Figures Appendix for examples of use)	C	Comp		Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.	M	ID	2/2	Must use

Syntax:

1. SLN04 P0405 -- If either SLN04 or SLN05 are present, then the others are required.

Semantics:

1. SLN01 is the identifying number for the subline item.
2. SLN02 is the identifying number for the subline level. The subline level is analogous to the level code used in a bill of materials.
3. SLN03 is the configuration code indicating the relationship of the subline item to the baseline item.
4. SLN08 is a code indicating the relationship of the price or amount to the associated segment.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. SLN01 is related to (but not necessarily equivalent to) the baseline item number. Example: 1.1 or 1A might be used as a subline number to relate to baseline number 1.
3. SLN09 through SLN28 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: CTT	Elements: 2

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items Description: Total number of line items in the transaction set	M	N0	1/6	Must use
CTT02	347	Hash Total Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example:-.0018 First occurrence of value beinghashed..18 Second occurrence of value beinghashed.1.8 Third occurrence of value beinghashed.18.01 Fourth occurrence of value beinghashed.-----1855 Hash total prior to truncation.855 Hash total after truncation tothree-digit field.	O	R	1/10	Used

Syntax:

1. CTT03 P0304 -- If either CTT03 or CTT04 are present, then the others are required.
2. CTT05 P0506 -- If either CTT05 or CTT06 are present, then the others are required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

AMT Monetary Amount

Pos: 020	Max: 1
Summary - Optional	
Loop: CTT	Elements: 3

To indicate the total monetary amount

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AMT01	522	Amount Qualifier Code Description: Code to qualify amount All valid standard codes are used.	M	ID	1/3	Must use
AMT02	782	Monetary Amount Description: Monetary amount	M	R	1/18	Must use
AMT03	478	Credit/Debit Flag Code Description: Code indicating whether amount is a credit or debit All valid standard codes are used.	O	ID	1/1	Used



SE

Transaction Set Trailer

Pos: 030	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments Description: Total number of segments included in a transaction set including ST and SE segments	M	N0	1/10	Must use
SE02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Comments:

- SE is the last segment of each transaction set.

GE**Functional Group Trailer**

Pos:	Max: 1
- Mandatory	
Loop: N/A	Elements: 2

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M	N0	1/6	Must use
GE02	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use

Semantics:

- The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

- The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA

Interchange Control Trailer

Pos:	Max: 1
- Mandatory	
Loop: N/A	Elements: 2

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups Description: A count of the number of functional groups included in an interchange	M	N0	1/5	Must use
IEA02	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	N0	9/9	Must use